SAFETY DATA SHEET

# PorceRAPID

## Component A (liquid)

Two-component fast-setting cement-based tile adhesive

| | |
|---|---|
| Product code | 1.TA.RAPID-A |
| Version | 2026.10 |
| Date of issue | 01/10/2026 |
| Revision date | Supersedes version 2026.07 |

Prepared in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) and the Vietnam Law on Chemicals No. 69/2025/QH15. This sheet contains the 16 mandatory sections in order.

BUMA-TA · TILE ADHESIVE

## 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE SUPPLIER

### 1.1 Product identifier

| | |
|---|---|
| Trade name | PorceRAPID — Component A (liquid) |
| Product code | 1.TA.RAPID-A |
| Product type | Liquid component (water-based polymer emulsion) of the PorceRAPID fast-setting tile adhesive set |
| Product classification | The product set achieves class C2F to TCVN 7899-1:2008 and EN 12004-1:2017 |
| Packaging | 33kg set (A: 8.0kg · B: 25kg) |

### 1.2 Relevant identified uses and uses advised against

**Identified use**: liquid component of the PorceRAPID two-component fast-setting tile adhesive set; to be mixed only with Component B (powder) in the ratio 7.5 - 8.0kg A / 25kg B.

**Uses advised against**: any application outside the manufacturer's technical instructions; do not mix with additives, cement, sand or other materials other than as instructed (see Section 7 and the product Technical Data Sheet).

### 1.3 Details of the supplier / manufacturer

**BUMATECH CO., LTD**

HEAD OFFICE
154/1/5 Cong Lo, Tan Son Ward, Ho Chi Minh City

OFFICE
91 Hoang Bat Dat, Tan Son Ward, Ho Chi Minh City

PLANT
820 Ap Chanh, Duc Lap Commune, Tay Ninh Province

TECHNICAL
0979 793 804

SALES
0914 765 778

EMAIL
bumagreen@bumatech.com.vn

WEBSITE
www.bumatech.vn

### 1.4 Emergency telephone number

**Medical emergency — 24/7**: **115** (national emergency number). Take this Safety Data Sheet or the product label with you to the medical facility.

**BUMATECH Technical Department**: 0979 793 804 (office hours) — advice on the product and on response measures.

## 2 HAZARD(S) IDENTIFICATION

### 2.1 Classification of the substance or mixture (GHS)

The product is NOT classified as a hazardous mixture under the GHS classification criteria (it does not meet the thresholds for physical, health or environmental hazards). The product is a synthetic polymer solution/dispersion in water, non-combustible, with a volatile organic compound (VOC) content of ≈ 0g/l.

### 2.2 GHS label elements

LABEL ELEMENTS

**NOT REQUIRED**

No hazard pictogram, signal word, hazard statement (H) or precautionary statement (P) is required under GHS.

### Safe-use recommendations — not required on the label

- Keep out of reach of children; keep away from food and drink.
- Wash hands after handling; avoid prolonged contact with skin and eyes.
- If splashed into the eyes: rinse with clean water for several minutes.
- Avoid release to the environment; dispose of the product and its packaging in accordance with applicable regulations.

### 2.3 Other hazards

- The product is a water-based polymer emulsion. Prolonged direct contact with the skin or eyes may cause mild to moderate irritation.
- Some predisposed individuals may develop an allergic skin reaction on frequent contact.
- Spilled product, or product that dries to a film, can make the work surface slippery.
- Mixing with Component B (cement-based powder) produces a strongly alkaline mixture that can cause skin irritation or burns and eye damage. When applying the mixed product, follow the protective measures set out in the Safety Data Sheet for Component B.
- The product does not meet the criteria for PBT (persistent, bioaccumulative, toxic) or vPvB.

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

| COMPONENT NAME | CAS / EC NO. | CONCENTRATION | CLASSIFICATION (GHS) |
|---|---|---|---|
| Polymer dispersion | Trade secret | Trade secret | Not classified |

No component is present at a concentration that would be classified as hazardous under the GHS criteria. The remainder consists of water and functional additives (stabilisers, preservatives, coalescing agents) at non-classifiable concentrations

## 4 FIRST-AID MEASURES

### 4.1 Description of necessary first-aid measures

**Skin contact**: Immediately remove contaminated clothing. Wash skin at once with soap and plenty of water. If irritation or a rash persists, get medical advice/attention.

**Eye contact**: Immediately rinse the eye under gently running clean water with the eyelids open for 10 - 15 minutes. Do not rub. Remove contact lenses if present and easy to do. Consult a doctor or ophthalmologist immediately.

**Ingestion**: Do not induce vomiting. Rinse mouth with water. Get medical advice immediately, showing the SDS and product label.

**Inhalation**: Move the person to fresh air, keep warm and at rest. If breathing difficulty persists, get medical advice.

### 4.2 Most important symptoms/effects, acute and delayed

Skin / eye irritation; repeated contact may cause skin sensitisation (allergic dermatitis); inhalation of vapour / mist may cause slight respiratory irritation.

### 4.3 Indication of immediate medical attention and special treatment

Treat symptomatically. No specific antidote is known. In the event of skin sensitisation, avoid further exposure.

## 5 FIRE-FIGHTING MEASURES

### 5.1 Extinguishing media

**Suitable media**: the water-based product is non-combustible; use media appropriate to the surrounding fire (water, foam, $CO_2$, dry powder).

**Unsuitable media**: none in particular.

### 5.2 Special hazards arising from the chemical

The product itself is non-combustible. Combustion of the dried polymer film may generate carbon monoxide (CO), $CO_2$ and smoke.

### 5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus (SCBA) where required in a smoky fire. Collect contaminated fire-extinguishing water separately.

## 6 ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Take care: surfaces wetted with the product are slippery. Wear gloves and safety goggles as required. Avoid prolonged eye contact.

### 6.2 Environmental precautions

Do not discharge the product into drains or water bodies (the preservative may be toxic to aquatic life and the product may block drains). Contain the spill.

### 6.3 Methods and material for containment and cleaning up

Absorb with inert material (sand, earth, absorbent granules); collect into suitable containers. Wipe clean while the product is still wet (once dry it forms a film that is hard to remove). Wash the area with water; retain the contaminated wash water for treatment.

## 7 HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid eye contact and prolonged skin contact; wash hands after handling. Shake or stir thoroughly before use. Dilute with water and mix at the correct dosage with cement, mortar or tile adhesive as instructed. Close the packaging after opening. Apply in a well-ventilated area.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a dry, cool place; PROTECT FROM FREEZING / FROST (water-based product — spoiled by freezing); keep away from direct sunlight and elevated temperatures. Keep out of reach of children and away from food.

**Shelf life:** 06 months in the unopened container (per the Technical Data Sheet).

**Incompatible materials:** strong acids, strong oxidisers; freezing temperatures.

### 7.3 Specific end use(s)

Liquid component of the PorceRAPID two-component tile adhesive set; to be used only for mixing with Component B (see Section 1 and the product Technical Data Sheet).

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters — occupational exposure limits (Vietnam)

The product contains no significant volatile components (VOC ≈ 0g/l); Vietnam has set no specific occupational exposure limit (OEL) for this additive. Apply general occupational hygiene principles per QCVN 02:2019/BYT and the Law on Occupational Safety and Health.

### 8.2 Individual protection measures (PPE)

No special protective equipment is required under normal conditions of use; apply good working practice.

**Eye protection**: Not required in normal use; wear safety goggles (EN 166) where there is a risk of splashing.

**Hand protection**: Not required for brief contact. For prolonged contact use gloves per EN ISO 374 — nitrile rubber (NBR) ≥ 0.35mm; neoprene / polychloroprene (CR) ≥ 0.5mm; butyl rubber (IIR) ≥ 0.5mm; fluoro rubber (FKM) ≥ 0.4mm; breakthrough time ≥ 480 minutes.

**Skin / body protection**: Standard protective clothing.

**Respiratory protection**: Not required under normal conditions of use.

**Engineering controls**: Ensure adequate general ventilation.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Physical state | Liquid |
| Colour | Milky white |
| Odour | Slight, characteristic |
| Odour threshold | No data available |
| pH | ≈ 10 |
| Melting/freezing point | ≈ 0°C (water-based — protect from freezing) |
| Boiling point | ≈ 100°C (water-based) |
| Flash point | Not applicable (water-based, non-combustible) |
| Flammability | Non-combustible |
| Vapour pressure | As for water (≈ 2.3kPa at 20°C) |
| Density | ≈ 1.03 ± 0.01g/cm³ |
| Solubility in water | Miscible / dispersible |
| Viscosity | Low (liquid) |
| VOC content | 0g/l |

## 10 STABILITY AND REACTIVITY

| | |
|---|---|
| 10.1 Reactivity | Stable under normal conditions. |
| 10.2 Chemical stability | Stable when stored correctly (cool and dry, protected from freezing). Freezing or elevated temperatures can break the emulsion (irreversible degradation). |
| 10.3 Possibility of hazardous reactions | No hazardous reactions occur. |
| 10.4 Conditions to avoid | Freezing; elevated temperatures; prolonged direct sunlight. |
| 10.5 Incompatible materials | Strong acids, strong oxidisers; concentrated electrolytes may coagulate the emulsion. |
| 10.6 Hazardous decomposition products | None under normal storage and use conditions. |

## 11 TOXICOLOGICAL INFORMATION

| ROUTE OF EFFECT | CLASSIFICATION RESULT |
|---|---|
| a) Acute toxicity | Not classified (criteria not met). |
| b) Skin corrosion/irritation | Not classified. Prolonged or repeated contact may cause mild to moderate irritation. |
| c) Serious eye damage/irritation | Not classified. May cause temporary stinging, redness and discomfort if splashed into the eyes. |
| d) Respiratory/skin sensitisation | Not classified. Predisposed individuals may show an allergic skin reaction on frequent contact (rare). |
| e) Germ cell mutagenicity | Not classified. |
| f) Carcinogenicity | Not classified. |
| g) Reproductive toxicity | Not classified. |
| h) STOT — single exposure | Not classified. |
| i) STOT — repeated exposure | Not classified. |
| j) Aspiration hazard | Not classified. |

## 12 ECOLOGICAL INFORMATION

| | |
|---|---|
| Toxicity | Not classified for environmental hazards. No component with hazardous environmental properties is present at the concentrations found in the product. Uncured product must nevertheless be kept out of water bodies. |
| Persistence and degradability | No data available; the synthetic polymer is persistent and poorly biodegradable. |
| Bioaccumulative potential | Not expected (high molecular weight polymer). |
| Mobility in soil | The dried product forms an inert film of low mobility. |
| Other adverse effects | Avoid releasing the product into water bodies and drains (it may block them once dry). |

## 13 DISPOSAL CONSIDERATIONS

- Minimise waste generation. Allow surplus product to dry (film-form / cure), then handle it as solid construction waste.
- Do not pour surplus product or wash water into drains (it may block them once dry).
- Dispose of in accordance with local and national regulations (the Law on Environmental Protection and applicable waste-management regulations).
- Empty packaging: clean or dispose of per regulations; do not reuse for other purposes.

## 14 TRANSPORT INFORMATION

Not classified as dangerous goods under transport regulations (ADR/RID for road and rail, IMDG for sea, IATA for air) or under domestic dangerous-goods transport regulations (Decree 161/2024/NĐ-CP).

| | |
|---|---|
| UN number | Not applicable |
| UN proper shipping name | Not applicable |
| Transport hazard class(es) | Not applicable |
| Packing group | Not applicable |
| Marine pollutant | None |

## 15 REGULATORY INFORMATION

### Vietnam

- Law on Chemicals No. 69/2025/QH15 (effective from 01/01/2026).
- Decree 24/2026/NĐ-CP, Decree 25/2026/NĐ-CP and Decree 26/2026/NĐ-CP.
- Circular 01/2026/TT-BCT and Circular 02/2026/TT-BCT of the Ministry of Industry and Trade.
- QCVN 02:2019/BYT — permissible dust exposure limits at the workplace.
- Decree 161/2024/NĐ-CP — transport of dangerous goods.
- Law on Occupational Safety and Health; applicable goods-labelling regulations.
- Classification and labelling per the Globally Harmonized System (GHS).

### International

- United Nations GHS (current edition).
- Reference product standards: EN 12004-1:2017 and TCVN 7899-1:2008 (class C2F).

**Chemical safety assessment:** not mandatory for this mixture.

## 16 OTHER INFORMATION

### Full text of the hazard (H) statements appearing in this SDS

None — the product is not classified as hazardous under GHS and contains no hazardous components.

### Legend to abbreviations

| | |
|---|---|
| CAS | Chemical Abstracts Service |
| EC / EINECS | European Community EINECS / ELINCS inventory |
| GHS | Globally Harmonized System of Classification and Labelling of Chemicals |
| OEL / TWA | Occupational exposure limit / time-weighted average / short-term |
| PBT / vPvB | Persistent, bioaccumulative, toxic / very persistent, very bioaccumulative |
| PPE | Personal protective equipment |

**Main data sources:** PorceRAPID Technical Data Sheet (version 2026.10); United Nations GHS.

**Disclaimer:** The information herein is based on our state of knowledge at the date stated and refers solely to the product indicated; it constitutes no guarantee of any particular property. It is the user's responsibility to ensure that this information is appropriate and complete for the specific intended use. This SDS cancels and replaces any preceding release.

END OF SAFETY DATA SHEET · 16 OF 16 SECTIONS